## DUCHESNE COUNTY MONUMENT SURVEY RECORD T1S R4W R3W DISTANCE SEC 25 | SEC 30 N 49°26'05" 47.84 N 70°35'31" 39.16 SEC 36 | SEC 31 S 55°20'51" W 52.31' L3 N 59°08'48 W 48.85 N 48°10'42" W 38.27 U.S.B.&M. E - 2536 S 89°17'12" W 5269.20' SEC 4000 NORTH COR PAVED COUNTY ROAD NOTE: THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT. 40'21'33.22670"N AND LONG. 110'17'38.91277"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER NORTH CANAL

### DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND MONUMENT (MAG) SPIKE IN ASPHALT COUNTY ROAD MATCHING TIES FROM PREVIOUS SURVEYS

# DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

SET 2½" DIA DUCHESNE COUNTY ALUM CAP ON 3/4"X30" REBAR FLUSH WITH ROAD SURFACE IN 5" CONCRETE COLLAR AT SECTION CORNER



SCALE: 1"=30'

*30'* 

MARKINGS ON MONUMENT

## STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE N: 7301981.180 F: 1981711.744 NAVD88 EL: 6360.70'

40°21'33.86921" N LATITUDE: 110°16′30.87306" W LONGITUDE:

ELLIPSOID HEIGHT: 6306.96' (GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300010S0040W0\_700200



PHOTO OF MONUMENT FACING SOUTH

#### CERTIFICATION

<u>Jerry D. Allred</u> , Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

11 DEC '17

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

